



Figura arriba = Grosor pared (pulg.) Figura bajo = Lbs / Pulg		ASME TUBERIA CEDULA															
Pipe Size	O.D. in. (mm)	5s	TRUE 5	10s	TRUE 10	20	30	40s & STD	TRUE 40	60	80s & XH	TRUE 80	100	120	140	160	XXH
1/8	0.405 (10.8)		0.035 0.1383	0.049 0.1863	0.049 0.1863		0.057 0.2120	0.068 0.2447	0.068 0.2447		0.095 0.3145	0.095 0.3145					
1/4	0.540 (13.7)		0.049 0.257	0.065 0.3297	0.065 0.3297		0.073 0.3644	0.088 0.4248	0.088 0.4248		0.119 0.5351	0.119 0.5351					
3/8	0.675 (17.1)		0.049 0.3276	0.065 0.4235	0.065 0.4235		0.073 0.4698	0.091 0.5676	0.091 0.5676		0.126 0.7388	0.126 0.7388					
1/2	0.840 (21.3)	0.065 0.5383	0.065 0.5383	0.083 0.671	0.083 0.671		0.095 0.7566	0.109 0.851	0.109 0.851		0.147 1.088	0.147 1.088				0.187 1.304	0.294 1.714
3/4	1.050 (26.7)	0.065 0.6838	0.065 0.6838	0.083 0.8572	0.083 0.8572		0.095 0.9699	0.113 1.131	0.113 1.131		0.154 1.474	0.154 1.474				0.218 1.937	0.308 2.441
1	1.315 (33.4)	0.065 0.8678	0.065 0.8678	0.109 1.404	0.109 1.404		0.114 1.464	0.133 1.679	0.133 1.679		0.179 2.172	0.179 2.172				0.250 2.844	0.358 3.659
1 1/4	1.660 (42.2)	0.065 1.107	0.065 1.107	0.109 1.806	0.109 1.806		0.117 1.930	0.140 2.273	0.140 2.273		0.191 2.997	0.191 2.997				0.250 3.765	0.382 5.214
1 1/2	1.900 (48.3)	0.065 1.274	0.065 1.274	0.109 2.087	0.109 2.087		0.125 2.372	0.145 2.718	0.145 2.718		0.200 3.631	0.200 3.631				0.281 4.859	0.400 6.408
2	2.375 (60.3)	0.065 1.604	0.065 1.604	0.109 2.638	0.109 2.638		0.125 3.007	0.154 3.653	0.154 3.653		0.218 5.022	0.218 5.022				0.344 7.462	0.436 9.029
2 1/2	2.875 (73.0)	0.083 2.475	0.083 2.475	0.120 3.531	0.120 3.531		0.188 5.400	0.203 5.793	0.203 5.793		0.276 7.661	0.276 7.661				0.375 10.01	0.552 13.70
3	3.500 (88.9)	0.083 3.029	0.083 3.029	0.120 4.332	0.120 4.332		0.188 6.656	0.216 7.576	0.216 7.576		0.300 10.25	0.300 10.25				0.437 14.32	0.600 18.58
3 1/2	4.000 (101.6)	0.083 3.472	0.083 3.472	0.120 4.970	0.120 4.970		0.188 7.661	0.226 9.109	0.226 9.109		0.318 12.51	0.318 12.51					0.636 22.85
4	4.500 (114.3)	0.083 3.915	0.083 3.915	0.120 5.613	0.120 5.613		0.188 8.666	0.237 10.79	0.237 10.79	0.281 12.66	0.337 14.98	0.337 14.98		0.437 19.01		0.531 22.51	0.674 27.54
4 1/2	5.000 (127.0)							0.247 12.53			0.355 17.61						0.710 32.53
5	5.563 (141.3)	0.109 6.349	0.109 6.349	0.134 7.770	0.134 7.770			0.258 14.62	0.258 14.62		0.375 20.78	0.375 20.78		0.500 27.04		0.625 32.96	0.750 38.55
6	6.625 (168.3)	0.109 7.585	0.109 7.585	0.134 9.289	0.134 9.289			0.280 18.97	0.280 18.97		0.432 28.57	0.432 28.57		0.562 36.39		0.718 45.30	0.864 53.16
7	7.625 (193.7)							0.301 23.57			0.500 38.05						0.875 62.08
8	8.625 (219.1)	0.109 9.914	0.109 9.914	0.148 13.40	0.148 13.40	0.250 22.36	0.277 24.70	0.322 28.55	0.322 28.55	0.406 35.64	0.500 43.39	0.500 43.39	0.593 50.87	0.718 60.63	0.812 67.76	0.906 74.69	0.875 72.42
9	9.625 (244.5)							0.342 33.90			0.500 48.72						
10	10.750 (273.0)	0.134 15.19	0.134 15.19	0.165 18.65	0.165 18.65	0.250 28.04	0.307 34.24	0.365 40.48	0.365 40.48	0.500 54.74	0.500 54.74	0.593 64.33	0.718 76.93	0.843 89.2	1.000 104.1	1.125 115.7	1.000 104.1
11	11.750 (298.4)							0.375 45.55			0.500 60.07						
12	12.750 (323.9)	0.156 21.07	0.165 22.18	0.180 24.20	0.180 24.20	0.250 33.38	0.330 43.77	0.375 49.56	0.406 53.53	0.562 73.16	0.500 65.42	0.687 88.51	0.843 107.2	1.000 125.5	1.125 139.7	1.312 160.3	1.000 125.5
14	14.000 (355.6)	0.156 23.06		0.188 27.73	0.250 36.71	0.312 45.68	0.375 54.57	0.375 54.57	0.437 63.67	0.593 84.91	0.500 72.09	0.750 106.1	0.937 130.7	1.093 150.7	1.250 170.2	1.406 189.1	1.000 138.8
16	16.000 (406.4)	0.165 27.90		0.188 31.75	0.250 42.05	0.312 52.36	0.375 62.58	0.375 62.58	0.500 82.77	0.656 107.5	0.500 82.77	0.843 136.5	1.031 164.8	1.218 192.3	1.437 223.5	1.593 245.1	1.000 160.2
18	18.000 (457)	0.165 31.43		0.188 35.76	0.250 47.39	0.312 59.03	0.437 82.06	0.375 70.59	0.562 104.8	0.750 138.2	0.500 93.45	0.937 170.8	1.156 208.0	1.375 244.1	1.562 274.2	1.781 308.5	1.000 181.6
20	20.000 (508)	0.188 39.78		0.218 46.05	0.250 52.73	0.375 78.60	0.500 104.1	0.375 78.60	0.593 122.9	0.812 166.4	0.500 104.1	1.031 208.9	1.281 256.1	1.500 296.4	1.750 341.1	1.968 379.0	1.000 202.9
22	22 (559)					0.375 86.61	0.500 114.8	0.375 86.61		0.875 197.4	0.500 114.8	1.125 250.8					1.000 224.3
24	24.000 (610)	0.218 55.37		0.250 63.41	0.250 63.41	0.375 94.62	0.562 140.8	0.375 94.62	0.687 171.2	0.968 238.1	0.500 125.5	1.218 296.4	1.531 367.4	1.812 429.4	2.062 483.1	2.343 541.9	1.000 245.6
26	26.000 (660)				0.312 85.60	0.500 136.2		0.375 102.6			0.500 136.2		Max custom WT 1.05 in				1.000 267.0
28	28.000 (711)				0.312 92.26	0.500 146.8	0.625 182.7	0.375 110.6			0.500 147.0		Max custom WT 0.97 in				
30	30.000 (762)	0.250 79.43		0.312 98.93	0.312 98.93	0.500 157.5	0.625 196.1	0.375 118.6			0.500 157.5		Max custom WT 0.90 in				
32	32.000 (813)				0.312 105.6	0.500 168.2	0.625 209.4	0.375 126.7	0.688 230.1		0.500 168.2		Max custom WT 0.85 in				
34	34.000 (864)				0.312 112.3	0.500 178.9	0.625 222.8	0.375 134.7	0.688 244.8		0.500 179.1		Max custom WT 0.80 in				
36	36.000 (914)				0.312 118.9		0.625 236.1	0.375 142.7	0.750 282.3		0.500 189.6		Max custom WT 0.75 in				